

Line reactor, three-phase **LR3 40-4/115**



Picture shows LR3 40-4/63

Advantages

Use as line reactor, commutating reactor or PFC reactor
Ensuring the short-circuit voltage of 3, 4 or 5 % to the mains
Power harmonic mitigation
Starting current limitation
Increases the service life of equipment
Low ripple
Bridging voltage dips
Peak current limitation
Very good corrosion protection and low noise due to vacuum impregnation
Integrated lifting rings
Multifunctional fixing rails

Applications

Line reactor to minimize mains pollution, to reduce the reactive-power components and charging currents in the DC link capacitor and to improve the cos(phi).

Standards

Line- and commutation reactor to
DIN EN 61558-2-20, IEC 61558-2-20, UL 506, CSA 22.2

Approvals



UL 506, CSA 22.2



Line reactor, three-phase LR3 40-4/115

Electrical data

Type	LR3 40-4/115
Operating data	
Rated voltage	3 x 400 Vac
Rated voltage (IEC)	3 x 690 Vac
Rated voltage (UL)	3 x 600 Vac
Short circuit voltage uK	4 % @ 400 Vac
Voltage drop	9.2 Vac
Rated current	3 x 115 A
Rated frequency	50 - 60 Hz
Inductance	0.26 mH
Inductance deviation	±10%
Output	
Power loss	331.2 W
Approvals	
Approvals	cURus
Environment	
Ambient temperature	14 °F to +104 °F
Type of cooling	AN
Safety and protection	
Type	Open type
Insulation class	IEC=F, UL=class 155
Protection index	IP 00
Safety class (prepared)	I
Test voltage	4000 Vac
Order numbers	
Order Number	LR3 40-4/115

Mechanical data

Type	LR3 40-4/115
Terminal and mounting	
Terminals phase	Flat copper
Connection type	for M8
Fixing method	Fixing rail
Fixing screws	M8
Measures and weights	
Weight	46.30 lbs

Dimensions in inch

