#### **RKD 20/2x24**



### Advantages

Minimum size at high power

Low weight

Dual input and dual output voltage for series or parallel connection

Minimal no-load losses

Outstanding temperature behavior due to low magnetic leakage field

Very low noise field


## **Applications**

As a mains transformer for adjustment of the voltage and simple electrical isolation

As an isolating transformer for the safe electrical isolation of the input and output sides. The transformer may be used to set up protective separation as a protective measure in accordance with VDE 0100.

As a safety isolating transformer for the safe electrical isolation of the input and output sides. The transformer is suitable for creating SELV and PELV circuits because of the limit on the output voltage.

# Sample application



Parallel connection (115V): brown with white/violet with blue Series connection (230V): violet with white

SEC:

Parallel connection: red with gresy/black with orange Series connection: black with grey

#### Standards

Mains transformer to: VDE 0570 Teil 2-1, DIN EN 61558-2-1, EN 61558-2-1, IEC 61558-2-1, UL 5085-1/-2, CSA 22.2 No.66 **Approvals** 



UL 5085-1/-2, CSA 22.2 No.66



Picture shows RKD 60 2x12



# Mains transformer **RKD 20/2x24**

|                 | Туре                            | RKD 20/2x24             |
|-----------------|---------------------------------|-------------------------|
| 3 ር             | Input                           |                         |
| 1+              | Rated input voltage             | 2 x 115 Vac             |
|                 | Rated frequency                 | 50 - 60 Hz              |
| Electrical data | Output                          |                         |
| g               | Rated output voltage            | 2 x 24 Vac              |
| ō               | Power                           | 20 VA                   |
| .은              | No-load voltage (app. x factor) | 1.29                    |
| 당               | No-load loss (typ.)             | 0.33 W                  |
| 쁦               | Efficiency                      | 77 %                    |
|                 | Standards                       |                         |
|                 | Classification                  | Mains transformer       |
|                 | Approvals                       |                         |
|                 | Approvals                       | cURus                   |
|                 | Environment                     |                         |
|                 | Ambient temperature max.        | 104.0 °F                |
|                 | Safety and protection           |                         |
|                 | Туре                            | Open type               |
|                 | Insulation class                | VDE=B, UL=class 105     |
|                 | Protection index                | IP 00                   |
|                 | Safety class (prepared)         | II .                    |
|                 | Short circuit strength          | non-short-circuit proof |
|                 | Test voltage                    | 4,000 Vac, 50 Hz        |
|                 | Order numbers                   |                         |
|                 | Order Number                    | RKD 20/2x24             |

|               | Type  | RKD 20/2x24              |
|---------------|---|--------------------------|
| 00.1          | Terminal and mounting                                     |                          |
| "' <b>.</b>   | Fixing method   | Mounting kit, M4 bolt    |
|               | Terminals   | Connecting leads, 200 mm |
| thanical data | Measures and weights                                      |                          |
| q             | Major diameter Ø  | 2.36 inch                |
| Ö             | Outside diameter in the area of the wire lead $\emptyset$ | 2.44 inch                |
| .9            | Height without mounting                                   | 1.22 inch                |
| ıя            | Weight  | 0.71 lbs                 |
| -             |   |                          |

